



US009637017B2

(12) **United States Patent**  
**Sung et al.**

(10) **Patent No.:** **US 9,637,017 B2**  
(45) **Date of Patent:** **May 2, 2017**

(54) **POWER-SHARING CHARGING SYSTEM,  
CHARGING DEVICE, AND METHOD FOR  
CONTROLLING THE SAME**

(58) **Field of Classification Search**  
CPC ..... B60L 11/1824  
(Continued)

(71) Applicant: **Korea Institute of Energy Research,**  
Daejeon (KR)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,803,215 A \* 9/1998 Henze ..... B60L 11/1811  
191/2  
7,256,516 B2 \* 8/2007 Buchanan ..... B60L 11/1811  
307/62

(Continued)

FOREIGN PATENT DOCUMENTS

KR 101009485 B1 1/2011  
KR 20110137675 A 12/2011

(Continued)

*Primary Examiner* — Drew A Dunn

*Assistant Examiner* — Jerry D Robbins

(74) *Attorney, Agent, or Firm* — Harness, Dickey &  
Pierce, P.L.C.

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 193 days.

(21) Appl. No.: **14/523,051**

(22) Filed: **Oct. 24, 2014**

(65) **Prior Publication Data**

US 2015/0115891 A1 Apr. 30, 2015

(30) **Foreign Application Priority Data**

Oct. 25, 2013 (KR) ..... 10-2013-0127520  
Jun. 30, 2014 (KR) ..... 10-2014-0081514

(51) **Int. Cl.**  
**B60L 11/18** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **B60L 11/1824** (2013.01); **Y02T 10/7005**  
(2013.01)

(57) **ABSTRACT**

The present disclosure provides a charging system including: at least two charging devices including at least two output units configured to supply connected automobiles with charging power, a first bus electrically connected to the output units and configured to transfer charging power to the output units, and a power processing unit configured to process power, which is supplied from a power source, using a first capacity and supply the first bus with the processed power; and a second bus configured to connect a first bus of a first charging device and a first bus of a second charging device, wherein, when a total capacity of charging power supplied to automobiles connected to the first charging device exceeds the first capacity, a part or all of lacking capacity is supplied via the second bus.

**17 Claims, 26 Drawing Sheets**

